

# Kubernetes klaszter telepítése

A telepített környezet három virtuális gépből áll:

- \*kub01\* (control plane): Almalinux 10 (x86\_64), minimal install (VCPU: 2, RAM: 3 GB, DISK: 20 GB)
- \*kub02\* (worker): Almalinux 10 (x86\_64), minimal install (VCPU: 2, RAM: 4 GB, DISK: 20 GB) \*
- \*kub03\* (worker): Almalinux 10 (x86\_64), minimal install (VCPU: 2, RAM: 4 GB, DISK: 20 GB)

A telepítéskor ne adjunk swap területet.

## Telepítést követő lépések

Az alábbi utasításokat a klaszter összes gépén le kell futtatni.

SELinux megengedő módba kapcsolása

```
# sed -i 's/^SELINUX=.*SELINUX=permissive/' /etc/selinux/config
# setenforce 0
```

Tűzfal szolgáltatás kikapcsolása és tiltása

```
# systemctl disable firewalld
Removed '/etc/systemd/system/multi-user.target.wants/firewalld.service'.
Removed '/etc/systemd/system/dbus-org.fedoraproject.FirewallD1.service'.

# systemctl stop firewalld
```

Hosts állományok módosítása

```
# cat > /etc/hosts <<'EOF'
127.0.0.1    localhost localhost.localdomain localhost4
localhost4.localhostdomain4
::1         localhost localhost.localdomain localhost6
localhost6.localhostdomain6

192.168.110.161 kube01
192.168.110.162 kube02
192.168.110.163 kube03
EOF
```

Containerd repo telepítése

```
# curl -L -o /etc/yum.repos.d/docker-ce.repo
https://download.docker.com/linux/centos/docker-ce.repo
```

Kubernetes repo létrehozása

```
# cat > /etc/yum.repos.d/kubernetes.repo <<'EOF'
[kubernetes]
name=Kubernetes
baseurl=https://pkgs.k8s.io/core:/stable:/v1.34/rpm/
enabled=1
gpgcheck=1
gpgkey=https://pkgs.k8s.io/core:/stable:/v1.34/rpm/repodata/repomd.xml.key
exclude=kubelet kubeadm kubectl cri-tools kubernetes-cni
EOF
```

Containerd telepítése

```
# dnf install containerd
```

Containerd konfiguráció mentése

```
# cp -a /etc/containerd/config.toml /etc/containerd/config.toml.orig
```

Containerd konfiguráció készítése

```
# containerd config default > /etc/containerd/config.toml
```

Containerd konfiguráció módosítása

```
# grep pause:3 /etc/containerd/config.toml
    sandbox_image = "registry.k8s.io/pause:3.8"

# sed -i 's/pause:3.8/pause:3.10.1/' /etc/containerd/config.toml

# grep pause:3 /etc/containerd/config.toml
    sandbox_image = "registry.k8s.io/pause:3.10.1"

# grep SystemdCgroup /etc/containerd/config.toml
    SystemdCgroup = false

# sed -i 's/SystemdCgroup = false/SystemdCgroup = true/'
/etc/containerd/config.toml

# grep SystemdCgroup /etc/containerd/config.toml
    SystemdCgroup = true
```

Containerd engedélyezése és indítása

```
# systemctl --now enable containerd
Created symlink '/etc/systemd/system/multi-
user.target.wants/containerd.service' →
'/usr/lib/systemd/system/containerd.service'.
```

Kubernetes klaszterhez szükséges csomagok telepítése

```
# dnf --disableexcludes=kubernetes install kubeadm kubect1 kubelet
```

Kubernetes kubelet szolgáltatás engedélyezése

```
# systemctl enable kubelet
```

## Control plane konfigurálása

Az alábbi utasításokat a control plane gépen kell futtatni

Klaszter init meghívása

```
# kubeadm init --pod-network-cidr=10.244.0.0/16
[init] Using Kubernetes version: v1.34.1
[preflight] Running pre-flight checks
[preflight] Pulling images required for setting up a Kubernetes cluster
[preflight] This might take a minute or two, depending on the speed of your
internet connection
[preflight] You can also perform this action beforehand using 'kubeadm
config images pull'
[certs] Using certificateDir folder "/etc/kubernetes/pki"
[certs] Generating "ca" certificate and key
[certs] Generating "apiserver" certificate and key
[certs] apiserver serving cert is signed for DNS names [kube01 kubernetes
kubernetes.default kubernetes.default.svc
kubernetes.default.svc.cluster.local] and IPs [10.96.0.1 192.168.110.161]
[certs] Generating "apiserver-kubelet-client" certificate and key
[certs] Generating "front-proxy-ca" certificate and key
[certs] Generating "front-proxy-client" certificate and key
[certs] Generating "etcd/ca" certificate and key
[certs] Generating "etcd/server" certificate and key
[certs] etcd/server serving cert is signed for DNS names [kube01 localhost]
and IPs [192.168.110.161 127.0.0.1 ::1]
[certs] Generating "etcd/peer" certificate and key
[certs] etcd/peer serving cert is signed for DNS names [kube01 localhost]
and IPs [192.168.110.161 127.0.0.1 ::1]
[certs] Generating "etcd/healthcheck-client" certificate and key
[certs] Generating "apiserver-etcd-client" certificate and key
[certs] Generating "sa" key and public key
[kubeconfig] Using kubeconfig folder "/etc/kubernetes"
[kubeconfig] Writing "admin.conf" kubeconfig file
[kubeconfig] Writing "super-admin.conf" kubeconfig file
[kubeconfig] Writing "kubelet.conf" kubeconfig file
[kubeconfig] Writing "controller-manager.conf" kubeconfig file
[kubeconfig] Writing "scheduler.conf" kubeconfig file
[etcd] Creating static Pod manifest for local etcd in
"/etc/kubernetes/manifests"
[control-plane] Using manifest folder "/etc/kubernetes/manifests"
[control-plane] Creating static Pod manifest for "kube-apiserver"
```

```
[control-plane] Creating static Pod manifest for "kube-controller-manager"
[control-plane] Creating static Pod manifest for "kube-scheduler"
[kubelet-start] Writing kubelet environment file with flags to file
"/var/lib/kubelet/kubeadm-flags.env"
[kubelet-start] Writing kubelet configuration to file
"/var/lib/kubelet/instance-config.yaml"
[patches] Applied patch of type "application/strategic-merge-patch+json" to
target "kubeletconfiguration"
[kubelet-start] Writing kubelet configuration to file
"/var/lib/kubelet/config.yaml"
[kubelet-start] Starting the kubelet
[wait-control-plane] Waiting for the kubelet to boot up the control plane as
static Pods from directory "/etc/kubernetes/manifests"
[kubelet-check] Waiting for a healthy kubelet at
http://127.0.0.1:10248/healthz. This can take up to 4m0s
[kubelet-check] The kubelet is healthy after 1.50097886s
[control-plane-check] Waiting for healthy control plane components. This can
take up to 4m0s
[control-plane-check] Checking kube-apiserver at
https://192.168.110.161:6443/livez
[control-plane-check] Checking kube-controller-manager at
https://127.0.0.1:10257/healthz
[control-plane-check] Checking kube-scheduler at
https://127.0.0.1:10259/livez
[control-plane-check] kube-controller-manager is healthy after 3.507200493s
[control-plane-check] kube-scheduler is healthy after 4.632817046s
[control-plane-check] kube-apiserver is healthy after 11.004003859s
[upload-config] Storing the configuration used in ConfigMap "kubeadm-config"
in the "kube-system" Namespace
[kubelet] Creating a ConfigMap "kubelet-config" in namespace kube-system
with the configuration for the kubelets in the cluster
[upload-certs] Skipping phase. Please see --upload-certs
[mark-control-plane] Marking the node kube01 as control-plane by adding the
labels: [node-role.kubernetes.io/control-plane node.kubernetes.io/exclude-
from-external-load-balancers]
[mark-control-plane] Marking the node kube01 as control-plane by adding the
taints [node-role.kubernetes.io/control-plane:NoSchedule]
[bootstrap-token] Using token: is490j.gmk4mrpb5aum3q8y
[bootstrap-token] Configuring bootstrap tokens, cluster-info ConfigMap, RBAC
Roles
[bootstrap-token] Configured RBAC rules to allow Node Bootstrap tokens to
get nodes
[bootstrap-token] Configured RBAC rules to allow Node Bootstrap tokens to
post CSRs in order for nodes to get long term certificate credentials
[bootstrap-token] Configured RBAC rules to allow the csrapprover controller
automatically approve CSRs from a Node Bootstrap Token
[bootstrap-token] Configured RBAC rules to allow certificate rotation for
all node client certificates in the cluster
[bootstrap-token] Creating the "cluster-info" ConfigMap in the "kube-public"
namespace
[kubelet-finalize] Updating "/etc/kubernetes/kubelet.conf" to point to a
```

```
rotatable kubelet client certificate and key
[addons] Applied essential addon: CoreDNS
[addons] Applied essential addon: kube-proxy
```

Your Kubernetes control-plane has initialized successfully!

To start using your cluster, you need to run the following as a regular user:

```
mkdir -p $HOME/.kube
sudo cp -i /etc/kubernetes/admin.conf $HOME/.kube/config
sudo chown $(id -u):$(id -g) $HOME/.kube/config
```

Alternatively, if you are the root user, you can run:

```
export KUBECONFIG=/etc/kubernetes/admin.conf
```

You should now deploy a pod network to the cluster.

Run "kubectl apply -f [podnetwork].yaml" with one of the options listed at:  
<https://kubernetes.io/docs/concepts/cluster-administration/addons/>

Then you can join any number of worker nodes by running the following on each as root:

```
kubeadm join 192.168.110.161:6443 --token is490j.gmk4mrpb5aum3q8y \
--discovery-token-ca-cert-hash
sha256:2454cd136d590b724210551fcb95ac360a2761f18a43729fe043eaf8dc139027
```

A kapcsolódáshoz szükséges konfiguráció beállítása

```
# mkdir -p $HOME/.kube
# sudo cp -i /etc/kubernetes/admin.conf $HOME/.kube/config
# sudo chown $(id -u):$(id -g) $HOME/.kube/config
```

Működés ellenőrzése

```
# kubectl get nodes
NAME      STATUS    ROLES    AGE   VERSION
kube01    NotReady  control-plane  11m   v1.34.1
```

Pod hálózat létrehozása (Flannel)

```
# kubectl apply -f
https://github.com/flannel-io/flannel/releases/latest/download/kube-flannel.
yaml
namespace/kube-flannel created
serviceaccount/flannel created
clusterrole.rbac.authorization.k8s.io/flannel created
clusterrolebinding.rbac.authorization.k8s.io/flannel created
```

```
configmap/kube-flannel-cfg created
daemonset.apps/kube-flannel-ds created
```

Rövid idő elteltével újabb ellenőrzés

```
# kubectl get nodes
NAME        STATUS    ROLES    AGE   VERSION
kube01     Ready    control-plane  2m    v1.34.1
```

## Worker gépek csatlakoztatása

Az alábbi utasításokat a worker gépeken kell futtatni

```
# kubeadm join 192.168.110.161:6443 --token is490j.gmk4mrpb5aum3q8y --
discovery-token-ca-cert-hash
sha256:2454cd136d590b724210551fcb95ac360a2761f18a43729fe043eaf8dc139027
[preflight] Running pre-flight checks
[preflight] Reading configuration from the "kubeadm-config" ConfigMap in
namespace "kube-system"...
[preflight] Use 'kubeadm init phase upload-config kubeadm --config your-
config-file' to re-upload it.
[kubelet-start] Writing kubelet configuration to file
"/var/lib/kubelet/instance-config.yaml"
[patches] Applied patch of type "application/strategic-merge-patch+json" to
target "kubeletconfiguration"
[kubelet-start] Writing kubelet configuration to file
"/var/lib/kubelet/config.yaml"
[kubelet-start] Writing kubelet environment file with flags to file
"/var/lib/kubelet/kubeadm-flags.env"
[kubelet-start] Starting the kubelet
[kubelet-check] Waiting for a healthy kubelet at
http://127.0.0.1:10248/healthz. This can take up to 4m0s
[kubelet-check] The kubelet is healthy after 1.004029985s
[kubelet-start] Waiting for the kubelet to perform the TLS Bootstrap
```

This node has joined the cluster:

- \* Certificate signing request was sent to apiserver and a response was received.
- \* The Kubelet was informed of the new secure connection details.

Run 'kubectl get nodes' on the control-plane to see this node join the cluster.

## Klaszter ellenőrzése

A klaszter ellenőrzését a control plane gépen végezzük el

```
# kubectl get nodes
```

| NAME   | STATUS | ROLES         | AGE  | VERSION |
|--------|--------|---------------|------|---------|
| kube01 | Ready  | control-plane | 12m  | v1.34.1 |
| kube02 | Ready  | <none>        | 4m5s | v1.34.1 |
| kube03 | Ready  | <none>        | 112s | v1.34.1 |

## Pod

Pod erőforrás dokumentáció megjelenítése

```
# kubectl explain pod
```

Egyszerű pod létrehozása egy konténerrel parancssorból

```
# kubectl run nginx-pod --image=nginx:latest --restart=Never
```

Egyszerű pod létrehozása egy konténerrel yaml fájlból

```
# cat > egyszeru-pod-egy-kontenerrel.yaml <<EOF
apiVersion: v1
kind: Pod
metadata:
  name: nginx-pod
spec:
  containers:
  - name: nginx
    image: nginx:latest
EOF
```

Konténer indítása

```
# kubectl apply -f egyszeru-pod-egy-kontenerrel.yaml
pod/nginx-pod created

# kubectl wait --for=condition=Ready pod/nginx-pod --timeout=90s
pod/nginx-pod condition met
```

Konténer ellenőrzése

```
# kubectl get pod/nginx-pod -o yaml
```

```
# kubectl describe pod/nginx-pod
Name:          nginx-pod
Namespace:     default
Priority:       0
Service Account: default
Node:          worker01.r-logic.eu/185.207.251.233
Start Time:    Tue, 16 Sep 2025 04:33:07 +0200
Labels:        run=nginx-pod
```

```
Annotations:      <none>
Status:           Running
IP:               10.244.1.14
IPs:
  IP: 10.244.1.14
Containers:
  nginx-pod:
    Container ID:
containerd://406b1f5856e2bfaa9e91d391078458c56e64c2f9d068f9b65dbab4d3c0b44e8
b
    Image:         nginx:latest
    Image ID:
nginx@sha256:d5f28ef21aabddd098f3dbc21fe5b7a7d7a184720bc07da0b6c9b9820e97f25
e
    Port:          <none>
    Host Port:     <none>
    State:         Running
      Started:     Tue, 16 Sep 2025 04:33:14 +0200
    Ready:         True
    Restart Count: 0
    Environment:   <none>
    Mounts:
      /var/run/secrets/kubernetes.io/serviceaccount from kube-api-access-
f79p9 (ro)
Conditions:
  Type                                Status
  PodReadyToStartContainers          True
  Initialized                         True
  Ready                              True
  ContainersReady                    True
  PodScheduled                       True
Volumes:
  kube-api-access-f79p9:
    Type:                            Projected (a volume that contains injected data
from multiple sources)
    TokenExpirationSeconds:          3607
    ConfigMapName:                   kube-root-ca.crt
    Optional:                        false
    DownwardAPI:                    true
QoS Class:                           BestEffort
Node-Selectors:                      <none>
Tolerations:                         node.kubernetes.io/not-ready:NoExecute
op=Exists for 300s
                                     node.kubernetes.io/unreachable:NoExecute
op=Exists for 300s
Events:
  Type    Reason      Age   From          Message
  ----    -
  Normal  Scheduled   53s   default-scheduler  Successfully assigned
default/nginx-pod to worker01.r-logic.eu
  Normal  Pulling     52s   kubelet        Pulling image "nginx:latest"
```

|        |         |     |         |                                                                                                            |
|--------|---------|-----|---------|------------------------------------------------------------------------------------------------------------|
| Normal | Pulled  | 46s | kubelet | Successfully pulled image "nginx:latest" in 5.622s (5.622s including waiting). Image size: 72319182 bytes. |
| Normal | Created | 46s | kubelet | Created container: nginx-pod                                                                               |
| Normal | Started | 46s | kubelet | Started container nginx-pod                                                                                |

Konténer nevének kiolvasása

```
# kubectl get pod/nginx-pod -o jsonpath='{.spec.containers[*].name}'
```

Utasítások futtatása a konténerben

```
# kubectl exec -it pod/nginx-pod -c nginx -- sh
```

Naplók megtekintése

```
# kubectl logs pod/nginx-pod
# kubectl logs pod/nginx-pod -c nginx
```

Port tesztelése

```
# kubectl port-forward pod/nginx-pod 8080:80
```

## Bővített pod definíció

```
# cat > bovitett-pod-egy-kontenerrel.yaml <<'EOF'
apiVersion: v1
kind: Pod
metadata:
  name: nginx-pod-advanced
  labels:
    app: nginx
spec:
  containers:
    - name: nginx
      image: nginx:1.25
      ports:
        - containerPort: 80
      resources:
        requests:
          cpu: "100m"
          memory: "128Mi"
        limits:
          cpu: "500m"
          memory: "256Mi"
      env:
        - name: NGINX_HOST
          value: "rl-hu"
```

```
- name: NGINX_PORT
  value: "80"
volumeMounts:
- name: nginx-html
  mountPath: /usr/share/nginx/html
volumes:
- name: nginx-html
  emptyDir: {}
nodeSelector:
  kubernetes.io/hostname: worker01.r-logic.eu
restartPolicy: Always
EOF
```

Bővített tartalom elemei

- **labels** → címkék, amelyekre később service-ek vagy deploymentek hivatkozhatnak
- **ports** → a konténeren belüli port meghatározása(TCP/80, HTTP)
- **resources** → CPU és memória foglалás minimum és maximum értékek
- **env** → környezeti változók beállítása
- **volumeMounts + volumes** → átmeneti tároló (emptyDir) csatolása a HTML tartalomnak
- **nodeSelector** → pod csak a worker01 gépen futhat
- **restartPolicy** → amennyiben megáll, újraindul

Egyszer használatos pod tesztelésekhez

```
# kubectl run debug-pod --rm -it --image=busybox:1.36 --restart=Never -- sh
```

# Deployment

## Létrehozás

Deployment létrehozása parancssorból

```
# kubectl create deployment nginx-deployment --image=nginx:latest && kubectl
wait --for=condition=Available deployment/nginx-deployment --timeout=90s
deployment.apps/nginx-deployment created
deployment.apps/nginx-deployment condition met
```

Deployment példányok módosítása

## Frissítés és visszaállítás

Deployment definíció

```
cat > nginx-deployment.yaml <<'EOF'
```

```
apiVersion: apps/v1
kind: Deployment
metadata:
  name: nginx-deployment
  annotations:
    kubernetes.io/change-cause: "Initial deploy: nginx 1.25"
spec:
  replicas: 3
  strategy:
    type: RollingUpdate
    rollingUpdate:
      maxSurge: 1
      maxUnavailable: 0
  selector:
    matchLabels:
      app: nginx
  template:
    metadata:
      labels:
        app: nginx
    spec:
      containers:
        - name: nginx
          image: nginx:1.25
          ports:
            - containerPort: 80
EOF

kubectl apply -f nginx-deployment.yaml
deployment.apps/nginx-deployment created
```

#### Frissítés 1.26-ra

```
# kubectl annotate deployment/nginx-deployment kubernetes.io/change-
cause="Upgrade to nginx 1.26" --overwrite
deployment.apps/nginx-deployment annotated

# kubectl set image deployment/nginx-deployment nginx=nginx:1.26
deployment.apps/nginx-deployment image updated

# kubectl rollout status deployment/nginx-deployment
Waiting for deployment "nginx-deployment" rollout to finish: 1 old replicas
are pending termination...
Waiting for deployment "nginx-deployment" rollout to finish: 1 old replicas
are pending termination...
deployment "nginx-deployment" successfully rolled out

# kubectl rollout history deployment/nginx-deployment
deployment.apps/nginx-deployment
REVISION  CHANGE-CAUSE
1          Upgrade to nginx 1.26
```

## 2 Upgrade to nginx 1.26

Frissítés 1.27-re

```
# kubectl rollout pause deployment/nginx-deployment

# kubectl annotate deployment/nginx-deployment kubernetes.io/change-
cause="Upgrade to nginx 1.27" --overwrite
deployment.apps/nginx-deployment annotated

# kubectl set image deployment/nginx-deployment nginx=nginx:1.27
deployment.apps/nginx-deployment image updated

# kubectl rollout resume deployment/nginx-deployment

# kubectl rollout status deployment/nginx-deployment
Waiting for deployment "nginx-deployment" rollout to finish: 1 out of 3 new
replicas have been updated...
Waiting for deployment "nginx-deployment" rollout to finish: 1 out of 3 new
replicas have been updated...
Waiting for deployment "nginx-deployment" rollout to finish: 1 out of 3 new
replicas have been updated...
Waiting for deployment "nginx-deployment" rollout to finish: 2 out of 3 new
replicas have been updated...
Waiting for deployment "nginx-deployment" rollout to finish: 2 out of 3 new
replicas have been updated...
Waiting for deployment "nginx-deployment" rollout to finish: 2 out of 3 new
replicas have been updated...
Waiting for deployment "nginx-deployment" rollout to finish: 1 old replicas
are pending termination...
Waiting for deployment "nginx-deployment" rollout to finish: 1 old replicas
are pending termination...
deployment "nginx-deployment" successfully rolled out

kubectl rollout history deployment/nginx-deployment
deployment.apps/nginx-deployment
REVISION  CHANGE-CAUSE
1          Upgrade to nginx 1.26
2          Upgrade to nginx 1.27
3          Upgrade to nginx 1.27

kubectl get replicaset -o wide
NAME                                DESIRED  CURRENT  READY  AGE      CONTAINERS
IMAGES                                SELECTOR
nginx-deployment-6585597c84         0         0        0      6m35s    nginx
nginx:1.26  app=nginx,pod-template-hash=6585597c84
nginx-deployment-6ccb84987c         3         3        3      2m58s    nginx
nginx:1.27  app=nginx,pod-template-hash=6ccb84987c
nginx-deployment-7bdc5996d7         0         0        0      7m27s    nginx
nginx:1.25  app=nginx,pod-template-hash=7bdc5996d7
```

Visszaállítás korábbi verzióra

```
# kubectl rollout undo deployment/nginx-deployment
deployment.apps/nginx-deployment rolled back

# kubectl get replicaset -o wide
NAME                                DESIRED    CURRENT    READY    AGE      CONTAINERS
IMAGES                                SELECTOR
nginx-deployment-6585597c84         3          3          3        12m      nginx
nginx:1.26    app=nginx,pod-template-hash=6585597c84
nginx-deployment-6ccb84987c         0          1          1        8m33s    nginx
nginx:1.27    app=nginx,pod-template-hash=6ccb84987c
nginx-deployment-7bdc5996d7         0          0          0        13m      nginx
nginx:1.25    app=nginx,pod-template-hash=7bdc5996d7
```

# Java/SpringBoot alkalmazás kubernetesbe költöztetése

## Alkalmazás elkészítése

```
# mkdir -p minimal-spring-k8s/src/main/java/com/example/demo

# cat > minimal-spring-
k8s/src/main/java/com/example/demo/DemoApplication.java <<'EOF'
package com.example.demo;

import org.springframework.boot.SpringApplication;
import org.springframework.boot.autoconfigure.SpringBootApplication;

@SpringBootApplication
public class DemoApplication {
    public static void main(String[] args) {
        SpringApplication.run(DemoApplication.class, args);
    }
}
EOF

# cat > minimal-spring-
k8s/src/main/java/com/example/demo/HomeController.java <<'EOF'
package com.example.demo;

import org.springframework.beans.factory.annotation.Value;
import org.springframework.stereotype.Controller;
import org.springframework.ui.Model;
import org.springframework.web.bind.annotation.GetMapping;
```

```
@Controller
public class HomeController {

    @Value("${SITE_TITLE:Alkalmazás}")
    private String siteTitle;

    @Value("${SITE_MESSAGE:Hello Kubernetes!}")
    private String siteMessage;

    @GetMapping("/")
    public String index(Model model) {
        model.addAttribute("title", siteTitle);
        model.addAttribute("message", siteMessage);
        return "index"; // templates/index.html
    }
}
EOF

# mkdir -p minimal-spring-k8s/src/main/resources/templates

# cat > minimal-spring-k8s/src/main/resources/templates/index.html <<'EOF'
<!doctype html>
<html lang="hu">
<head>
<meta charset="UTF-8" />
<meta name="viewport" content="width=device-width, initial-scale=1" />
<title th:text="${title}">Alkalmazás</title>
<style>
body { font-family: system-ui, -apple-system, Segoe UI, Roboto, Ubuntu,
Cantarell, 'Helvetica Neue', Arial, 'Noto Sans', 'Apple Color Emoji', 'Segoe
UI Emoji', 'Segoe UI Symbol';
margin: 0; padding: 2rem; background: #0f172a; color: #e2e8f0; }
.card { max-width: 680px; margin: 10vh auto; background: #111827; border-
radius: 16px; padding: 2rem; box-shadow: 0 10px 40px rgba(0,0,0,0.35); }
h1 { margin: 0 0 1rem; font-size: 2rem; }
p { margin: 0 0 1rem; font-size: 1.125rem; }
small { opacity: .7; }
code { background: #0b1020; padding: .25rem .4rem; border-radius: .4rem; }
</style>
</head>
<body>
<main class="card">
<h1 th:text="${title}">Alkalmazás</h1>
<p th:text="${message}">Hello Kubernetes!</p>
<small>Forrás: ConfigMap → env → @Value → Thymeleaf</small>
</main>
</body>
</html>
EOF

# cat > minimal-spring-k8s/src/main/resources/application.properties <<'EOF'
```

```
# Spring Boot alapbeállítások
server.port=${PORT:8080}
server.shutdown=graceful

# Actuator health végpont a kubernetes ellenőrzéshez
management.endpoints.web.exposure.include=health,info
management.endpoint.health.probes.enabled=true
EOF

# cat > minimal-spring-k8s/pom.xml <<'EOF'
<project xmlns="http://maven.apache.org/POM/4.0.0"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="http://maven.apache.org/POM/4.0.0
http://maven.apache.org/xsd/maven-4.0.0.xsd">
  <modelVersion>4.0.0</modelVersion>
  <groupId>com.example</groupId>
  <artifactId>minimal-spring-k8s</artifactId>
  <version>0.0.1-SNAPSHOT</version>
  <name>minimal-spring-k8s</name>
  <description>Minimal Spring Boot app for Kubernetes with
ConfigMap</description>

  <properties>
    <java.version>21</java.version>
    <spring-boot.version>3.3.4</spring-boot.version>
  </properties>

  <dependencyManagement>
    <dependencies>
      <dependency>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-dependencies</artifactId>
        <version>${spring-boot.version}</version>
        <type>pom</type>
        <scope>import</scope>
      </dependency>
    </dependencies>
  </dependencyManagement>

  <dependencies>
    <dependency>
      <groupId>org.springframework.boot</groupId>
      <artifactId>spring-boot-starter-web</artifactId>
    </dependency>
    <dependency>
      <groupId>org.springframework.boot</groupId>
      <artifactId>spring-boot-starter-thymeleaf</artifactId>
    </dependency>
    <dependency>
      <groupId>org.springframework.boot</groupId>
```

```
<artifactId>spring-boot-starter-actuator</artifactId>
</dependency>
<dependency>
  <groupId>org.springframework.boot</groupId>
  <artifactId>spring-boot-starter-test</artifactId>
  <scope>test</scope>
</dependency>
</dependencies>

<build>
  <plugins>
    <plugin>
      <groupId>org.springframework.boot</groupId>
      <artifactId>spring-boot-maven-plugin</artifactId>
      <executions>
        <execution>
          <goals>
            <goal>repackage</goal>
          </goals>
        </execution>
      </executions>
    </plugin>
    <plugin>
      <groupId>org.apache.maven.plugins</groupId>
      <artifactId>maven-compiler-plugin</artifactId>
      <configuration>
        <release>21</release>
      </configuration>
    </plugin>
  </plugins>
</build>
</project>
EOF
```

Alkalmazás fordítása a teszteléshez

```
# cd minimal-spring-k8s

# mvn clean package
[INFO] Scanning for projects...
...
[INFO] -----
---
[INFO] BUILD SUCCESS
[INFO] -----
---
[INFO] Total time: 4.565 s
[INFO] Finished at: 2025-09-17T07:09:50+02:00
[INFO] -----
---
```

Elkészült a **minimal-spring-k8s/target/minimal-spring-k8s-0.0.1-SNAPSHOT.jar** alkalmazás.

## Konténer image készítése

Első megoldás: mindig friss alkalmazás készítése:

```
# cd minimal-spring-k8s

# cat > Dockerfile <<'EOF'
# Alkalmazás fordítása
FROM maven:3.9.8-eclipse-temurin-21-alpine AS build
WORKDIR /app
COPY pom.xml .
RUN mvn -q -e -B -DskipTests dependency:go-offline
COPY src ./src
RUN mvn -q -e -B -DskipTests package

# Konténer image készítés
FROM eclipse-temurin:21-jre-alpine
WORKDIR /app

# Spring Boot alkalmazás másolása
COPY --from=build /app/target/minimal-spring-k8s-*.jar app.jar

# A Spring Boot a PORT env változót ismeri
ENV PORT=8080
EXPOSE 8080

# JVM opciók konténeres környezethez
ENV JAVA_OPTS="-XX:+UseContainerSupport -XX:MaxRAMPercentage=75"
ENTRYPOINT ["sh", "-c", "java $JAVA_OPTS -jar app.jar"]
EOF
```

Másik megoldás: a már meglévő build használata

```
# cat > Dockerfile <<'EOF'
# Konténer image készítése
FROM eclipse-temurin:21-jre-alpine
WORKDIR /app

# Spring Boot alkalmazás másolása
COPY target/minimal-spring-k8s-*.jar app.jar
```

```
# A Spring Boot a PORT env változót ismeri
ENV PORT=8080
EXPOSE 8080

# JVM opciók konténeres környezethez
ENV JAVA_OPTS="-XX:+UseContainerSupport -XX:MaxRAMPercentage=75"
ENTRYPOINT ["sh", "-c", "java $JAVA_OPTS -jar app.jar"]
EOF
```

### Konténer image készítése

```
# podman build -t minimal-spring-k8s:0.0.1 .
STEP 1/7: FROM eclipse-temurin:21-jre-alpine
STEP 2/7: WORKDIR /app
--> 45811f6fd665
STEP 3/7: COPY target/minimal-spring-k8s-*.jar app.jar
--> 9d027583908b
STEP 4/7: ENV PORT=8080
--> d8b7374f93ea
STEP 5/7: EXPOSE 8080
--> 5468f35be894
STEP 6/7: ENV JAVA_OPTS="-XX:+UseContainerSupport -XX:MaxRAMPercentage=75"
--> bec2bb2e08e7
STEP 7/7: ENTRYPOINT ["sh", "-c", "java $JAVA_OPTS -jar app.jar"]
COMMIT minimal-spring-k8s:0.0.1
--> f0d688f68506
Successfully tagged localhost/minimal-spring-k8s:0.0.1
f0d688f685065441108f94b6460d7ca3917c7f444d2a07a9993ac7f561a4f4e3
```

### Image előkészítése és a registry-be töltése

```
# podman image tag localhost/minimal-spring-k8s:0.0.1 REGISTRY_URL/minimal-
spring-k8s:0.0.1

# podman push REGISTRY_URL/minimal-spring-k8s:0.0.1
Getting image source signatures
Copying blob cba3fb5670d7 done      |
Copying blob a6af48261b3d done      |
Copying blob 27d41fb27db9 done      |
Copying blob 4ac76939e813 done      |
Copying blob df603300ccbc done      |
Copying blob a5048fclae11 done      |
Copying config f0d688f685 done      |
Writing manifest to image destination
```

## Kubernetes configmap, deployment, service definíciók elkészítése

```
# mkdir k8s
```

```
# cat >k8s/configmap.yaml <<'EOF'
apiVersion: v1
kind: ConfigMap
metadata:
  name: minimal-spring-config
  labels:
    app: minimal-spring-k8s
data:
  SITE_TITLE: "Kubernetesből jövő cím"
  SITE_MESSAGE: "Ez az üzenet ConfigMap-ból érkezik."
EOF

# cat > k8s/deployment.yaml <<'EOF'
apiVersion: apps/v1
kind: Deployment
metadata:
  name: minimal-spring-k8s
  labels:
    app: minimal-spring-k8s
spec:
  replicas: 2
  selector:
    matchLabels:
      app: minimal-spring-k8s
  strategy:
    type: RollingUpdate
    rollingUpdate:
      maxUnavailable: 0
      maxSurge: 1
  template:
    metadata:
      labels:
        app: minimal-spring-k8s
    spec:
      terminationGracePeriodSeconds: 30
      containers:
        - name: app
          image: REGISTRY_URL/minimal-spring-k8s:0.0.1
          imagePullPolicy: IfNotPresent
          ports:
            - name: http
              containerPort: 8080
          envFrom:
            - configMapRef:
                name: minimal-spring-config
          startupProbe:
            httpGet:
              path: /actuator/health/liveness
              port: 8080
            failureThreshold: 30
            periodSeconds: 2
```

```

    readinessProbe:
      httpGet:
        path: /actuator/health/readiness
        port: 8080
      initialDelaySeconds: 5
      periodSeconds: 10
      timeoutSeconds: 2
      failureThreshold: 3
    livenessProbe:
      httpGet:
        path: /actuator/health/liveness
        port: 8080
      initialDelaySeconds: 10
      periodSeconds: 20
      timeoutSeconds: 2
      failureThreshold: 3
    resources:
      requests:
        cpu: "100m"
        memory: "128Mi"
      limits:
        memory: "512Mi"

```

EOF

```
# cat > k8s/service.yaml <<'EOF'
```

```
apiVersion: v1
```

```
kind: Service
```

```
metadata:
```

```
  name: minimal-spring-k8s
```

```
  labels:
```

```
    app: minimal-spring-k8s
```

```
spec:
```

```
  type: NodePort
```

```
  selector:
```

```
    app: minimal-spring-k8s
```

```
  ports:
```

```
    - name: http
```

```
      nodePort: 30001
```

```
      port: 80
```

```
      targetPort: 8080
```

EOF

## Kubernetes műveletek

```
# kubectl get all
```

| NAME               | TYPE      | CLUSTER-IP | EXTERNAL-IP | PORT(S) | AGE |
|--------------------|-----------|------------|-------------|---------|-----|
| service/kubernetes | ClusterIP | 10.96.0.1  | <none>      | 443/TCP | 43h |

```
# kubectl apply -f k8s/configmap.yaml
```

```
configmap/minimal-spring-config created
```

```
# kubectl apply -f k8s/deployment.yaml
deployment.apps/minimal-spring-k8s created

# kubectl apply -f k8s/service.yaml
service/minimal-spring-k8s created

# kubectl get all,cm
NAME                                                    READY   STATUS    RESTARTS   AGE
pod/minimal-spring-k8s-6d956c4c9f-n6rb2                1/1     Running   0           4m33s
pod/minimal-spring-k8s-6d956c4c9f-vj8tc                1/1     Running   0           4m33s
```

| NAME                       | TYPE      | CLUSTER-IP   | EXTERNAL-IP |
|----------------------------|-----------|--------------|-------------|
| service/kubernetes         | ClusterIP | 10.96.0.1    | <none>      |
| service/minimal-spring-k8s | NodePort  | 10.106.11.23 | <none>      |

```
PORT(S)          AGE
443/TCP          43h
```

| NAME                               | READY | UP-TO-DATE | AVAILABLE | AGE   |
|------------------------------------|-------|------------|-----------|-------|
| deployment.apps/minimal-spring-k8s | 2/2   | 2          | 2         | 4m33s |

| NAME                                          | AGE   | DESIRED | CURRENT | READY |
|-----------------------------------------------|-------|---------|---------|-------|
| replicaset.apps/minimal-spring-k8s-6d956c4c9f | 4m33s | 2       | 2       | 2     |

| NAME                            | DATA | AGE   |
|---------------------------------|------|-------|
| configmap/kube-root-ca.crt      | 1    | 43h   |
| configmap/minimal-spring-config | 2    | 4m40s |

Módosítások a configmap tartalmában

```
# cat > k8s/configmap.yaml <<'EOF'
apiVersion: v1
kind: ConfigMap
metadata:
  name: minimal-spring-config
  labels:
    app: minimal-spring-k8s
data:
  SITE_TITLE: "Kubernetesből jövő új cím"
  SITE_MESSAGE: "Ez az üzenet az úrből érkezett."
EOF

# kubectl apply -f k8s/configmap.yaml
configmap/minimal-spring-config configured

# kubectl rollout restart deployment/minimal-spring-k8s
deployment.apps/minimal-spring-k8s restarted

# kubectl get all
```

| NAME                                    | READY | STATUS  | RESTARTS | AGE   |
|-----------------------------------------|-------|---------|----------|-------|
| pod/minimal-spring-k8s-5d757fcb88-km5bn | 1/1   | Running | 0        | 5m26s |
| pod/minimal-spring-k8s-5d757fcb88-rtfrv | 1/1   | Running | 0        | 5m41s |

  

| NAME                       | TYPE      | CLUSTER-IP    | EXTERNAL-IP |
|----------------------------|-----------|---------------|-------------|
| service/kubernetes         | ClusterIP | 10.96.0.1     | <none>      |
| service/minimal-spring-k8s | NodePort  | 10.98.248.233 | <none>      |

  

| NAME                               | READY | UP-TO-DATE | AVAILABLE | AGE |
|------------------------------------|-------|------------|-----------|-----|
| deployment.apps/minimal-spring-k8s | 2/2   | 2          | 2         | 33m |

  

| NAME                                          | DESIRED | CURRENT | READY |
|-----------------------------------------------|---------|---------|-------|
| replicaset.apps/minimal-spring-k8s-57d696db7c | 0       | 0       | 0     |
| replicaset.apps/minimal-spring-k8s-5d757fcb88 | 2       | 2       | 2     |

## Kubernetes natív LB megoldás

A konfigurálást a control plane gépen végezzük el

MetallB telepítése

```
# kubectl apply -f
https://raw.githubusercontent.com/metallb/metallb/v0.13.12/config/manifests/
metallb-native.yaml
namespace/metallb-system created
customresourcedefinition.apiextensions.k8s.io/addresspools.metallb.io
created
customresourcedefinition.apiextensions.k8s.io/bfdprofiles.metallb.io created
customresourcedefinition.apiextensions.k8s.io/bgpadvertisements.metallb.io
created
customresourcedefinition.apiextensions.k8s.io/bgppeers.metallb.io created
customresourcedefinition.apiextensions.k8s.io/communities.metallb.io created
customresourcedefinition.apiextensions.k8s.io/ipaddresspools.metallb.io
created
customresourcedefinition.apiextensions.k8s.io/l2advertisements.metallb.io
created
serviceaccount/controller created
serviceaccount/speaker created
role.rbac.authorization.k8s.io/controller created
role.rbac.authorization.k8s.io/pod-lister created
clusterrole.rbac.authorization.k8s.io/metallb-system:controller created
clusterrole.rbac.authorization.k8s.io/metallb-system:speaker created
```

```
rolebinding.rbac.authorization.k8s.io/controller created
rolebinding.rbac.authorization.k8s.io/pod-lister created
clusterrolebinding.rbac.authorization.k8s.io/metallb-system:controller
created
clusterrolebinding.rbac.authorization.k8s.io/metallb-system:speaker created
configmap/metallb-excludel2 created
secret/webhook-server-cert created
service/webhook-service created
deployment.apps/controller created
daemonset.apps/speaker created
validatingwebhookconfiguration.admissionregistration.k8s.io/metallb-webhook-
configuration created
```

### Publikus IP tartomány megadása

```
# cat > ~/metallb-l2.yaml <<'EOF'
apiVersion: metallb.io/v1beta1
kind: IPAddressPool
metadata:
  name: pool-l2
  namespace: metallb-system
spec:
  addresses:
    - 192.168.110.170-192.168.110.179
---
apiVersion: metallb.io/v1beta1
kind: L2Advertisement
metadata:
  name: l2adv
  namespace: metallb-system
spec:
  ipAddressPools:
    - pool-l2
EOF
```

### MetallB podjainak ellenőrzése

```
# kubectl -n metallb-system get pods
```

| NAME                        | READY | STATUS  | RESTARTS | AGE   |
|-----------------------------|-------|---------|----------|-------|
| controller-7dbf649dcc-w4frr | 1/1   | Running | 0        | 2m17s |
| speaker-4nkqt               | 1/1   | Running | 0        | 2m17s |
| speaker-q4h2p               | 1/1   | Running | 0        | 2m17s |
| speaker-vxp69               | 1/1   | Running | 0        | 2m17s |

### Konfiguráció alkalmazása (amennyiben a pod-ok Ready/Running állapotban vannak)

```
# kubectl apply -f metallb-l2.yaml
ipaddresspool.metallb.io/pool-l2 created
l2advertisement.metallb.io/l2adv created
```

## A metallb-system névtér ellenőrzése

```
# kubectl get all -n metallb-system
```

| NAME                            | READY | STATUS  | RESTARTS | AGE |
|---------------------------------|-------|---------|----------|-----|
| pod/controller-7dbf649dcc-w4frr | 1/1   | Running | 0        | 49m |
| pod/speaker-4nkqt               | 1/1   | Running | 0        | 49m |
| pod/speaker-q4h2p               | 1/1   | Running | 0        | 49m |
| pod/speaker-vxp69               | 1/1   | Running | 0        | 49m |

| NAME                    | TYPE      | CLUSTER-IP    | EXTERNAL-IP | PORT(S) |
|-------------------------|-----------|---------------|-------------|---------|
| service/webhook-service | ClusterIP | 10.104.247.76 | <none>      | 443/TCP |

| NAME                   | DESIRED | CURRENT | READY | UP-TO-DATE | AVAILABLE |
|------------------------|---------|---------|-------|------------|-----------|
| daemonset.apps/speaker | 3       | 3       | 3     | 3          | 3         |

| NAME                       | READY | UP-TO-DATE | AVAILABLE | AGE |
|----------------------------|-------|------------|-----------|-----|
| deployment.apps/controller | 1/1   | 1          | 1         | 49m |

| NAME                                  | DESIRED | CURRENT | READY | AGE |
|---------------------------------------|---------|---------|-------|-----|
| replicaset.apps/controller-7dbf649dcc | 1       | 1       | 1     | 49m |

## Teszt deployment létrehozása és ellenőrzése

```
# kubectl create deploy nginx --image=nginx:stable --port=80
deployment.apps/nginx created
```

```
# kubectl expose deploy nginx --type=LoadBalancer --port=80 --target-port=80
service/nginx exposed
```

```
# kubectl get svc nginx
```

| NAME  | TYPE         | CLUSTER-IP   | EXTERNAL-IP     | PORT(S)      | AGE |
|-------|--------------|--------------|-----------------|--------------|-----|
| nginx | LoadBalancer | 10.109.25.42 | 192.168.110.170 | 80:31422/TCP | 13s |

Amennyiben megjelent az EXTERNAL-IP oszlopban a definiált tartomány egyik IP címe, akkor tesztelhető a szolgáltatás

```
# curl -I http://192.168.110.170
HTTP/1.1 200 OK
Server: nginx/1.28.0
Date: Thu, 25 Sep 2025 17:17:34 GMT
Content-Type: text/html
Content-Length: 615
Last-Modified: Wed, 23 Apr 2025 11:48:54 GMT
Connection: keep-alive
ETag: "6808d3a6-267"
Accept-Ranges: bytes
```

From:

<http://wiki.r-l.hu/> - **Reverse-Logic wiki**

Permanent link:

<http://wiki.r-l.hu/doku.php?id=kubernetes:gyakorlatok&rev=1759305422>

Last update: **2025/10/01 07:57**

